

TER HOME PRODUCT

ATHERTON COLLECTION SPECIFICATIONS

MATTE BLACK FINISH






BHP) ITEM# BP02PAS44BLK - Passage Set


BHMA Grade III passage set. Solid zinc cast construction. Door Prep - Crossbore 2 1/8", Edge Bore 1", Latch Face 1"x2 1/4" Door Thickness - 1 3/8" to 1 3/4"

Function: Both levers always free

Strike - Full lip radius corner standard. Other options available Latch - 1/2" throw bolt, 2 3/8" or 2 3/4" backset adjustable. Radius corner face plate standard. Other options available

Door Handing - Reversible






BHP) ITEM# BP02PRIV44BLK - Privacy Set

BHMA Grade III privacy set. Solid zinc cast construction. Door Prep - Crossbore 2 1/8", Edge Bore 1", Latch Face 1"x2 1/4" Door Thickness - 1 3/8" to 1 3/4"

Function - Outside lever locked by push button inside, inside lever always free. Also can be opened by emergency key out side Strike - Full lip radius corner standard. Other options available Latch - 1/2" throw bolt, 2 3/8" or 2 3/4" backset adjustable. Radius corner face plate standard. Other options available





(BHP)

ITEM# BP02DUM44BLK - Dummy Lever


BHMA Grade III dummy lever. Solid zinc cast construction. **Door Prep** - Surface mounted with 2 exposed mounting screws. No door prep needed

Door Thickness - greater than 1"

Function: Active lever, for doors where only a pull / push is required.

Door Handing - Reversible







BHP) ITEM# BP02TRIM44BLKRT/LT - Handleset Trim Plate

BHMA Grade III handleset trim lever, works for all BHP offering handlesets (5.5" C-C). Solid zinc cast construction.

Door Prep - See BHP handleset door prep

Door Thickness - 1 3/8" to 1 3/4" Function: Lever always free Door Handing - Handed.





BHP)

ITEM# BP02DEA44BLK - Deadbolt Passage Set

All metal components with inner anti-pick shield

Door Prep - Crossbore 2 1/8", Edge Bore 1", Latch Face 1"x2 1/4"

Door Thickness - 1 3/8" to 1 3/4"

Center to Center: 5.5 '

Function: Locked or unlocked by key out side or turn-piece inside.

Cylinder - 5 pin KW1 keyway. Other options available

Strike - Full lip radius corner standard. Other options available Latch - 2 3/8" or 2 3/4" backset adjustable. Radius corner face plate

standard. Other options available